



AAAACME RUBBER CO.

A Division of Fillipone Enterprises Inc.

2003 E. 5th Street, #1

Tempe, AZ 85288

Phone: 480-966-9311 Email: info@acmerubber.com

SPECIFICATION SHEET: COMPOUND #46160

TECHNICAL DATA

Property	Value
Polymer Content	Blend of Nitrile Rubber & PVC
Temperature Range	-30° to +225°F
Hardness, Shore A	65 ± 5
Tensile Strength (PSI)	1050
Elongation (%)	450%

MATERIAL DESCRIPTION

AAA-Acme Rubber #46160 is a high-performance blend of nitrile rubber and polyvinyl chloride plastic, processed under high-temperature conditions to ensure optimal material integrity. This compound offers exceptional weather and oil resistance and is formulated to maintain a stable white color.

FDA Compliance: All ingredients used in this compound are listed as approved by the FDA in 21 CFR 177.2600 for repeated food exposure.

THE DATA PRESENTED IS BASED ON TESTING AND TO OUR KNOWLEDGE IS ACCURATE. SINCE APPLICATIONS, TEST METHODS AND PROCEDURES MAY VARY, WE RECOMMEND THAT USERS OF OUR PRODUCT PERFORM THEIR OWN TESTS TO ASSURE THE SUITABILITY OF THESE PRODUCTS FOR THEIR APPLICATION. WE OFFER NO PRODUCT WARRANTY, EITHER EXPRESSED OR IMPLIED, EXCEPT ANY PRODUCT PROVEN DEFECTIVE WILL BE REPLACED. FREEDOM FROM PRESENT OR FUTURE INFRINGEMENT CANNOT BE GUARANTEED, NOR CAN THE SUITABILITY FOR A SPECIFIC APPLICATION.